

### Technical Sheet RU151HD

Easypurge RU151HD is an innovative purging compound formulated with a special blend of low-abrasive inorganic fillers and organic additives on a high-viscosity HDPE carrier, specifically developed for cleaning extrusion and injection lines. It facilitates optimal cleaning of screws, dies, and nozzles during color changes and/or polymer transitions.

### Product Description

Easypurge RU151HD acts very efficiently as a cleaning compound, reaching all internal dead zones of the extruder where polymer and contaminants tend to stagnate, effortlessly removing residual pigments, fillers, and degraded materials accumulated inside the equipment.

The compound's excellent thermal stability also allows for extended machine downtime, even at elevated temperatures, preventing premature thermo-oxidative degradation that results in oxidized particles formed during extruder downtime or during scheduled shutdowns, and eliminating the need for additional disassembly for cleaning.

Easypurge RU151HD barely adheres to metal surfaces, allowing easy removal of adhered material during off-line cleaning.

### Main uses and applications

Easypurge RU151HD has been specially developed for both off-line and on-line cleaning operations, even making it possible to film the product without stopping the line during cleaning processes.

The product can be used in processes with temperatures between 160°C and 240°C, although the best performance is achieved at temperatures below 160°C. It is especially suitable for material transitions, color changes, shutdown operations, and periodic cleaning of polyolefin lines. In addition to polyolefins, it is also compatible with other polymers, depending on the compatibility and viscosity of the polymer, as well as the process temperatures.

Recommended applications:

Aplicaciones	PE	PP	Estirénicos	PVC Rígido	PMMA	Polímeros Técnicos
Film Cast & Soplado	****	**				
Extrusión soplado	****	****				
Extrusión de perfiles & lámina	****	****		**	**	**
Extrusión de tubería	***	***		**		
Cables	***	***		**		***
Inyección	****	**	**	**	**	**

For other situations, it is recommended to contact our technical department.

### Regulations

Easypurge RU151HD only contains substances approved for contact with food, in accordance with European legislation.

### **Storage and packaging**

Store the product in a dry place at room temperature, protected from direct sunlight. Under normal conditions, the average shelf life is one year. The product is supplied in 25 kg PE bags.

### **Legal information**

To provide the data and/or information contained in this communication, Qootzeer Innovation Lab SL has relied on its current knowledge and experience, and therefore cannot guarantee that these data and/or information will meet the recipient's intended specifications. In any case, please note that these data and/or information have no contractual value, unless expressly provided by Qootzeer Innovation. Lab SL. Please note that all values, processes, and technical information submitted by Qootzeer Innovation Lab SL are exclusively valid for the uses and applications specifically determined for each case, as all of them may be subject to alterations depending on the testing and uses carried out by the recipient. Please note that the recipient or final recipient of such data and/or information is responsible for performing all necessary checks to verify the suitability of the data and/or information prior to its industrial use, including compliance with current legislation at all times. The supplier is not liable for any damages, claims, indemnities, compensation, and other negative consequences that may be caused to the recipient due to incorrect use of the data and/or information provided, and, in any case, when the warnings contained in this section are ignored.